

View Online at <https://aerobasegroup.com/nsn/5945-01-134-8032>

Overall Length:

2.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility

Overall Height:

3.131 inches

Overall Width:

2.440 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.168 inches single mounting facility and 0.175 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac motor load and 40.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

11 solder stud all functions

Specification Data:

96906-ms27751 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.