NSN 5945-01-136-3986

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-136-3986

Overall Length:
3.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches single mounting facility
Overall Height:
2.250 inches
Mounting Slot Width:
0.200 inches single mounting facility
Unthreaded Mounting Hole Diameter:
0.191 inches single mounting facility and 0.206 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility and 1 slotted hole single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
2.375 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
284.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
Main Contact Load Current Rating At Maximum Rated Voltage:
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity:
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 5 threaded stud all functions
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 5 threaded stud all functions Shelf Life:
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 5 threaded stud all functions Shelf Life: N/a
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 5 threaded stud all functions Shelf Life: N/a
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 5 threaded stud all functions Shelf Life: N/a Unit Of Measure:
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 5 threaded stud all functions Shelf Life: N/a Unit Of Measure: Demilitarization:
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 5 threaded stud all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No