# NSN 5945-01-137-0160

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-137-0160

# Overall Length:

1.718 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Overall Height:** 

1.635 inches

**Overall Width:** 

0.525 inches

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.155 inches single mounting facility and 0.161 inches single mounting facility

#### Winding Quantity:

2

#### **Coil Quantity:**

2

#### Winding Dc Resistance Rating:

600.0 ohms all windings

# **Duty Type:**

Continuous

# **Mounting Facility Type And Quantity:**

2 unthreaded hole single mounting facility

#### **Features Provided:**

Latching contacts and polarized

# **Mounting Facility Pattern:**

In-line single mounting facility

# **Nonpile-up Main Contact Arrangement:**

1 pole, double throw, one position momentary

#### Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

# Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac motor load and 10.0 amperes dc motor load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

7 wire hook all functions

#### **Specification Data:**

81349-mil-r-6106/20 government specification

# Shelf Life:

N/a

# NSN 5945-01-137-0160

Electromagnetic Relay - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-6106 spec.