## NSN 5945-01-138-1342

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-138-1342

Overall Diameter: Between 0.275 inches and 0.335 inches Environmental Protection: Hermetic Winding Quantity: 1 Cotil Quantity: 1 Winding Dc Resistance Rating: 1.56 ohns single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Noppli-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 28.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: Brist-q-mil-r-390169's specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: Na Unit Of Measure: — Demilitarization: No Filig: A03300	
Overall Diameter: Betwenn 0.275 inches and 0.335 inches Environmental Protection: Hormoelic Winding Quantity:  1 Coli Quantity: 1 Winding Dc Resistance Rating: 1.56 ohns single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationlified Temp: 25.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating in Volts: 28.0 dc Test Data Document: 81349-mili-r39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: No Unit Of Measure: — Demilitarization: No Flig:	Overall Length:
Between 0.275 inches and 0.335 inches  Environmental Protection:  Harmatic  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:  1.56 ohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  1 terminal single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp:  28.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-milr-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification commar; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  Na  Unit Of Measure:  —  Demilitarization:  No  Flig:	
Environmental Protection: Hermetic Winding Quantity:  1 Coil Quantity: 1 Winding Dc Resistance Rating: 1.56 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: Main Contact Arrangement: 2.50 yolts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact United Maximum Voltage Rating In Volts: 1.0 amperes dc resistive load Main Contact United Maximum Voltage Rating In Volts: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 am	
Hemetic Winding Quantity: 1 Coli Quantity: 1 Winding Dc Resistance Rating: 1.56 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 25.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: 81349-milr-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: N/a Unit Of Measure:	Between 0.275 inches and 0.335 inches
Winding Quantity:  1 Coil Quantity:  1 Winding Dc Resistance Rating: 1.56 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 25.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes do resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: N/a Unit Of Measure:	Environmental Protection:
Coil Quantity:  1 Winding Dc Resistance Rating: 1.56 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts do 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes do resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hermetic
Coil Quantity:  1 Winding Dc Resistance Rating: 1.56 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Winding Quantity:
Winding Dc Resistance Rating: 1.56 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 2.5. volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	1
Winding Dc Resistance Rating:  1.56 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 1 terminal single mounting facility  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts: 28.0 dc  Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 wire lead all functions  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Coil Quantity:
1.56 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts do 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes do resistive load  Main Contact Maximum Voltage Rating In Volts: 28.0 dc  Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:  Demilitarization: No Fiig:	1
Duty Type: Continuous  Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts do 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes do resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: 81349-mil39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: N/a Unit Of Measure:	Winding Dc Resistance Rating:
Continuous  Mounting Facility Type And Quantity:  1 terminal single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  Na  Unit Of Measure:   Demilitarization:  No  Fig:	1.56 ohms single winding
Mounting Facility Type And Quantity:  1 terminal single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Duty Type:
1 terminal single mounting facility  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts: 28.0 dc  Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 wire lead all functions  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Continuous
Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Mounting Facility Type And Quantity:
2 pole, double throw, one position momentary  Time Delay:  0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	1 terminal single mounting facility
Time Delay:  0.002 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts: 28.0 dc  Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 wire lead all functions  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Nonpile-up Main Contact Arrangement:
O.002 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 wire lead all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Time Delay:
26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	0.002 seconds fixed operate time
Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Operating Voltage Rating And Type At Specificationified Temp:
1.0 amperes dc resistive load  Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	26.5 volts dc 25 degrees celsius single winding
Main Contact Maximum Voltage Rating In Volts:  28.0 dc  Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Main Contact Load Current Rating At Maximum Rated Voltage:
28.0 dc  Test Data Document: 81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 wire lead all functions  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	1.0 amperes dc resistive load
Test Data Document:  81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Main Contact Maximum Voltage Rating In Volts:
81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	28.0 dc
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	81349-mil-r-39016/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Terminal Type And Quantity:  8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
8 wire lead all functions  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	8 wire lead all functions
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A03300	Fiig:
	A03300