## NSN 5945-01-138-3195

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-138-3195

| view Online at https://aerobasegroup.com/nsn/5945-01-136-3195  |
|--|
| Overall Length:  |
| 7.969 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                 |
| 5.312 inches single mounting facility  |
| Overall Height:  |
| 3.600 inches   |
| Overall Width:   |
| 6.250 inches   |
| Case Material:   |
| Metal  |
| Unthreaded Mounting Hole Diameter:   |
| 0.406 inches single mounting facility  |
| Fragility Factor:  |
| Moderately rugged  |
| Winding Quantity:  |
| 1  |
| Purpose For Which Designed:  |
| General  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 2.5 kilohms single winding   |
| Duty Type:   |
| Continuous   |
| Arc Quenching Method:  |
| Air  |
| Mounting Facility Type And Quantity:   |
| 3 unthreaded hole single mounting facility   |
| Storage Type:  |
| General purpose warehouse  |
| Cubic Measure:   |
| 179.303 cubic inches   |
| Mounting Facility Pattern:   |
| Triangle single mounting facility  |
| Nonpile-up Main Contact Arrangement:   |
| 2 pole, double throw, one position momentary   |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 7.437 inches single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 24.0 volts dc 25 degrees celsius single winding  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |

1.0 amperes ac resistive load

## NSN 5945-01-138-3195

Electromagnetic Relay - Page 2 of 2



## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Terminal Type And Quantity:** 

8 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300