# NSN 5945-01-138-7262

Electromagnetic Relay - Page 1 of 2

Overall Length: 1.280 inches

Overall Height: 0.850 inches Overall Width: 0.410 inches

**Mounting Slot Width:** 

**Case Material:** 

Time Delay:

115.0 ac and 28.0 dc

0.004 seconds fixed operate and release time

28.0 volts dc 25 degrees celsius single winding

**Operating Voltage Rating And Type At Specificationified Temp:** 

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

Metal

0.133 inches single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-01-138-7262

Center To Center Distance Between Mounting Facilities Parallel To Length: 1.062 inches single mounting facility and 1.078 inches single mounting facility

Environmental Protection:	
Hermetic	
Fragility Factor:	
Moderately rugged	
Winding Quantity:	
1	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
500.0 ohms single winding	
Duty Type:	
Continuous	
Mounting Facility Type And Quantity:	
2 slotted hole single mounting facility	
Storage Type:	
General purpose warehouse	
Features Provided:	
Coil voltage suppression and polarized	
Mounting Facility Pattern:	
In-line single mounting facility	
Nonpile-up Main Contact Arrangement:	
2 pole, double throw, one position momentary	

## NSN 5945-01-138-7262

Electromagnetic Relay - Page 2 of 2



#### **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

8 wire hook all functions

### **Specification Data:**

81349-mil-r-6106/27 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300