

View Online at <https://aerobasegroup.com/nsn/5945-01-139-0889>

Overall Length:

1.180 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.125 inches single mounting facility

Overall Height:

0.612 inches

Overall Width:

0.410 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.096 inches single mounting facility

Contact Material:

Metal

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

2.07 kilohms single winding and 3.85 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

50.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300