NSN 5945-01-141-1969

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-141-1969

| Thread Class: |
|---|
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 0.800 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.412 inches single mounting facility |
| Overall Height: |
| 0.938 inches |
| Overall Width: |
| 0.400 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic and vibration resistant |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 2 |
| Winding Dc Resistance Rating: |
| 1.0 kilohms all windings |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 threaded stud single mounting facility |
| Features Provided: |
| Latching contacts and polarized |
| Cubic Measure: |
| 0.300 cubic inches |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.004 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |

26.5 volts dc 25 degrees celsius all windings

NSN 5945-01-141-1969

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300