

View Online at <https://aerobasegroup.com/nsn/5945-01-146-3366>

Overall Length:

4.343 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.687 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility

Overall Height:

3.956 inches

Overall Width:

4.156 inches

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, double make, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

150.0 amperes ac resistive load and 150.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac motor load and 5.0 amperes dc motor load

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 threaded stud all functions

Specification Data:

96906-ms27715 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.