NSN 5945-01-146-6692

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-146-6692

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

2.375 inches

Overall Width:

1.000 inches

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Frequency In Hertz:

400.0

Winding Quantity:

Coil Quantity:

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Cubic Measure:

2.968 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.05 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

109.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

NSN 5945-01-146-6692

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300