## NSN 5945-01-146-6692

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-146-6692

**Thread Class:** 

2a single mounting facility

**Thread Direction:** 

Right-hand single mounting facility

**Overall Length:** 

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

0.625 inches single mounting facility

**Overall Height:** 

2.375 inches

**Overall Width:** 

1.000 inches

**Environmental Protection:** 

Hermetic and shock resistant and vibration resistant

Frequency In Hertz:

400.0

**Winding Quantity:** 

**Coil Quantity:** 

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 threaded stud single mounting facility

**Cubic Measure:** 

2.968 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

**Thread Size:** 

0.112 inches single mounting facility

**Mounting Facility Pattern:** 

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

Time Delay:

0.05 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

109.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

## NSN 5945-01-146-6692

Electromagnetic Relay - Page 2 of 2



## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 30.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300