

View Online at <https://aerobasegroup.com/nsn/5945-01-147-8068>

Thread Class:

2a first mounting facility

Overall Length:

6.719 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches second mounting facility

Overall Height:

3.094 inches

Overall Width:

5.406 inches

Mounting Slot Width:

0.219 inches second mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole second mounting facility

Thread Size:

0.190 inches first mounting facility

Mounting Facility Pattern:

In-line second mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

600.0 milliamperes ac single winding

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

600.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

70.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

600.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

Thread Series Designator:

Unf first mounting facility

Terminal Type And Quantity:

12 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300