## NSN 5945-01-147-8069

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-147-8069

**Thread Class:** 2a first mounting facility **Overall Length:** 7.000 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 2.000 inches second mounting facility **Overall Height:** 3.281 inches **Overall Width:** 4.625 inches **Mounting Slot Width:** 0.219 inches second mounting facility Frequency In Hertz: 60.0 Winding Quantity: **Coil Quantity: Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 slotted hole second mounting facility **Thread Size:** 0.190 inches first mounting facility **Mounting Facility Pattern:** In-line second mounting facility **Nonpile-up Main Contact Arrangement:** 4 pole, single throw, normally open, momentary action **Operating Current Rating And Type:** 600.0 milliamperes ac single winding **Nonpile-up Auxiliary Contact Arrangement:** 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action **Auxiliary Contact Maximum Voltage Rating In Volts:** 600.0 ac **Operating Voltage Rating And Type At Specificationified Temp:** 70.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 25.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 600.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:** 

5.0 amperes ac resistive load

## NSN 5945-01-147-8069

Electromagnetic Relay - Page 2 of 2



Unf first mounting facility

**Terminal Type And Quantity:** 

14 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300