

View Online at <https://aerobasegroup.com/nsn/5945-01-149-1160>

Overall Length:

1.188 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

Overall Height:

1.125 inches

Overall Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.125 inches single mounting facility

Contact Material:

Gold

End Application:

Los angeles class ssn (688), sturgeon class ssn (637), nimitz class cvn, Forrestal class cv, strategic weapon systems (poseidon & trident), general purpose electronic test equipment gpete

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

400.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Weapon system essential

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Terminal Type And Quantity:

5 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300