NSN 5945-01-149-1160

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-149-1160

Overall Length:
1.188 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches single mounting facility
Overall Height:
1.125 inches
Overall Width:
0.750 inches
Unthreaded Mounting Hole Diameter:
0.125 inches single mounting facility
Contact Material:
Gold
End Application:
Los angeles class ssn (688), sturgeon class ssn (637), nimitz class cvn, forrestal class cv, strategic weapon systems (poseidon & trident),
general purpose electronic test equipment gpete
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
400.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Weapon system essential

Precious Material And Location:

Contacts gold

Precious Material:

Gold

NSN 5945-01-149-1160

Electromagnetic Relay - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

5 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300