

View Online at <https://aerobasegroup.com/nsn/5945-01-149-7382>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.177 inches single mounting facility

Overall Length:

1.172 inches

Overall Height:

1.384 inches

Overall Width:

0.735 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold

End Application:

Visual approved slope indicator lighting system (vasi)

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

185.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

48 single mounting facility

Thread Size:

0.099 inches single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

30.0 milliamperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 26.0 dc

Energizing Element Power Rating:

2.6 watts

Special Features:

Function, relay, electromagnetic; reference data, ti-6850.46a, fa-9898,

Precious Material And Location:

Contacts silver and 0contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300