

View Online at <https://aerobasegroup.com/nsn/5945-01-149-7382>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Thread Length:**

0.177 inches single mounting facility

**Overall Length:**

1.172 inches

**Overall Height:**

1.384 inches

**Overall Width:**

0.735 inches

**Case Material:**

Plastic

**Environmental Protection:**

Dustproof

**Fragility Factor:**

Moderately rugged

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold

**End Application:**

Visual approved slope indicator lighting system (vasi)

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

185.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 threaded stud single mounting facility

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

48 single mounting facility

**Thread Size:**

0.099 inches single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Operating Current Rating And Type:**

30.0 milliamperes dc single winding

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 26.0 dc

**Energizing Element Power Rating:**

2.6 watts

**Special Features:**

Function, relay, electromagnetic; reference data, ti-6850.46a, fa-9898,

**Precious Material And Location:**

Contacts silver and 0contact surfaces gold

**Precious Material:**

Silver and gold

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300