NSN 5945-01-150-4560

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-150-4560 **Overall Length:** 1.320 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.060 inches single mounting facility **Overall Width:** 0.605 inches **Environmental Protection:** Hermetic and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches single mounting facility Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 870.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 unthreaded hole single mounting facility **Mounting Facility Pattern:** In-line single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 30.0 dc **Energizing Element Power Rating:** 600.0 milliwatts **Terminal Type And Quantity:** 8 wire hook all functions Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5945-01-150-4560

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300