

View Online at <https://aerobasegroup.com/nsn/5945-01-150-6296>

Overall Length:

8.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.125 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.125 inches single mounting facility

Overall Height:

6.130 inches

Overall Width:

6.810 inches

Environmental Protection:

Shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.213 inches single mounting facility and 0.228 inches single mounting facility

Frequency In Hertz:

400.0

Winding Quantity:

2

Coil Quantity:

2

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Cubic Measure:

367.776 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, single throw, normally open, double make, momentary action and 2 pole, single throw, normally closed, double break, momentary action and 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

Time Delay:

0.10 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

350.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Terminal Type And Quantity:

19 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300