NSN 5945-01-150-6310

Electrical Solenoid - Page 1 of 2

Body Style: Open frame



View Online at https://aerobasegroup.com/nsn/5945-01-150-6310

| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | | | |
|---|--|--|--|--|--|--|
| 2.000 inches | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | | | | | | |
| Between 1.605 inches and 1.645 inches | | | | | | |
| Mounting Slot Width: | | | | | | |
| 0.208 inches | | | | | | |
| Body Length: | | | | | | |
| 2.500 inches | | | | | | |
| Body Width: | | | | | | |
| Between 2.042 inches and 2.082 inches | | | | | | |
| Body Height: | | | | | | |
| Between 2.063 inches and 2.103 inches | | | | | | |
| Frequency In Hertz: | | | | | | |
| 60.0 | | | | | | |
| Inclosure Type: | | | | | | |
| Uninclosed | | | | | | |
| Magnetic Coil Quantity: | | | | | | |
| 1 | | | | | | |
| Duty Type: | | | | | | |
| Intermittent | | | | | | |
| Terminal Location: | | | | | | |
| One side | | | | | | |
| Voltage Rating In Volts: | | | | | | |
| 115.0 ac | | | | | | |
| Mounting Facility Type And Quantity: | | | | | | |
| 4 slot | | | | | | |
| Actuator Stroke Type: | | | | | | |
| Pull | | | | | | |
| Linear Force Delivered: | | | | | | |
| 12.50 pounds | | | | | | |
| Power Takeoff Connection Type: | | | | | | |
| Tee shape w/clevis groove | | | | | | |
| Energizing Stroke Maximum Length: | | | | | | |
| 1.072 inches | | | | | | |
| Mounting Facility Pattern: | | | | | | |
| Four position rectangular | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 2 screw | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 5945-01-150-6310

Electrical Solenoid - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A134a0