

View Online at <https://aerobasegroup.com/nsn/5945-01-150-8533>

**Overall Length:**

1.280 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches single mounting facility

**Overall Height:**

0.860 inches

**Overall Width:**

0.810 inches

**Mounting Slot Width:**

0.133 inches single mounting facility

**Environmental Protection:**

Shock resistant and vibration resistant

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

400.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Features Provided:**

Polarized

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.062 inches single mounting facility and 1.078 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Special Features:**

Case grounded

**Terminal Type And Quantity:**

14 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300