NSN 5945-01-152-6991

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-152-6991
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.375 inches
Overall Height:
1.397 inches
Overall Width:
0.735 inches
Environmental Protection:
Dustproof
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Winding Quantity:
2
Coil Quantity:
2
Winding Dc Resistance Rating:
350.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 threaded stud single mounting facility
Thready Qty Per Inch (tpi):
48 single mounting facility
Thread Size:
0.099 inches single mounting facility
Nonpile-up Main Contact Arrangement:
6 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
24.0 volts ac 25 degrees celsius single winding
24.0 volts ac 25 degrees celsius single winding
24.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
24.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load
24.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
24.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc

Silver and gold

NSN 5945-01-152-6991

Electromagnetic Relay - Page 2 of 2



Thread	Series	Design	ator

Unc single mounting facility

Terminal Type And Quantity:

22 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300