NSN 5945-01-152-8971

Electromagnetic Relay - Page 1 of 2

Overall Length: 6.875 inches



View Online at https://aerobasegroup.com/nsn/5945-01-152-8971

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 5.875 inches single mounting facility |
|--|
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.750 inches single mounting facility |
| Overall Height: |
| 6.750 inches |
| Overall Width: |
| 5.625 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dripproof and shock resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.469 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 26.104 cubic inches |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, single throw, normally open, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 440.0 volts ac 25 degrees celsius single winding |
| |

NSN 5945-01-152-8971

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

400.0 ac

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300