

View Online at <https://aerobasegroup.com/nsn/5945-01-156-7742>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

1.165 inches

**Overall Height:**

1.407 inches

**Overall Width:**

0.735 inches

**Environmental Protection:**

Dustproof

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold flash

**Winding Quantity:**

2

**Coil Quantity:**

2

**Winding Dc Resistance Rating:**

100.0 ohms first winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 threaded stud single mounting facility

**Features Provided:**

Latching contacts

**Thready Qty Per Inch (tpi):**

48 single mounting facility

**Thread Size:**

0.099 inches single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius all windings

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300