## NSN 5945-01-156-7745

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-156-7745

Overall Length:
1.062 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches single mounting facility
Overall Height:
0.320 inches
Overall Width:
0.310 inches
Unthreaded Mounting Hole Diameter:
0.096 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
44.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Features Provided:
Polarized
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
5.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Established reliability
Test Data Document:
81349-mil-r-39016/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 wire hook all functions
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5945-01-156-7745

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300