

View Online at <https://aerobasegroup.com/nsn/5945-01-157-0293>

Overall Length:

Between 0.790 inches and 0.810 inches

Overall Height:

Between 0.597 inches and 0.617 inches

Overall Width:

Between 0.390 inches and 0.410 inches

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

2

Winding Dc Resistance Rating:

1.0 kilohms all windings

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized and latching contacts

Cubic Measure:

0.205 cubic inches

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.005 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

160.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level 1. Percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 pin all functions

Specification Data:

81349-mil-r-39016/45 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300