## NSN 5945-01-157-0357

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-157-0357 **Thread Class:** 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 2.062 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches single mounting facility **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.500 inches single mounting facility **Overall Height:** 2.213 inches **Overall Width:** 2.062 inches **Case Material:** Metal **Environmental Protection:** Hermetic and shock resistant and vibration resistant Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 92.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility **Cubic Measure:** 9.409 cubic inches Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility **Nonpile-up Main Contact Arrangement:** 4 pole, double throw, one position momentary Time Delay: 0.025 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-157-0357

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 15.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

14 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300