## NSN 5945-01-157-4611

Electromagnetic Relay - Page 1 of 2

115.0 ac and 28.0 dc



View Online at https://aerobasegroup.com/nsn/5945-01-157-4611

| Inread Class:   |  |  |  |  |  |
|---|--|--|--|--|--|
| 2a single mounting facility   |  |  |  |  |  |
| Thread Direction:   |  |  |  |  |  |
| Right-hand single mounting facility   |  |  |  |  |  |
| Overall Length:   |  |  |  |  |  |
| 1.594 inches  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                              |  |  |  |  |  |
| 0.375 inches single mounting facility   |  |  |  |  |  |
| Overall Height:   |  |  |  |  |  |
| 1.638 inches  |  |  |  |  |  |
| Overall Width:  |  |  |  |  |  |
| 1.500 inches  |  |  |  |  |  |
| Fragility Factor:   |  |  |  |  |  |
| Moderately rugged   |  |  |  |  |  |
| Winding Quantity:   |  |  |  |  |  |
| 1   |  |  |  |  |  |
| Purpose For Which Designed:   |  |  |  |  |  |
| General   |  |  |  |  |  |
| Coil Quantity:  |  |  |  |  |  |
| 1   |  |  |  |  |  |
| Duty Type:  |  |  |  |  |  |
| Continuous  |  |  |  |  |  |
| Arc Quenching Method:   |  |  |  |  |  |
| Air   |  |  |  |  |  |
| Mounting Facility Type And Quantity:  |  |  |  |  |  |
| 2 threaded stud single mounting facility  |  |  |  |  |  |
| Storage Type:   |  |  |  |  |  |
| General purpose warehouse   |  |  |  |  |  |
| Thready Qty Per Inch (tpi):   |  |  |  |  |  |
| 32 single mounting facility   |  |  |  |  |  |
| Thread Size:  |  |  |  |  |  |
| 0.138 inches single mounting facility   |  |  |  |  |  |
| Mounting Facility Pattern:  |  |  |  |  |  |
| In-line single mounting facility  |  |  |  |  |  |
| Nonpile-up Main Contact Arrangement:  |  |  |  |  |  |
| 2 pole, double throw, one position momentary  |  |  |  |  |  |
| Operating Voltage Rating And Type At Specificationified Temp:   |  |  |  |  |  |
| 115.0 volts ac 25 degrees celsius single winding and 220.0 volts dc 25 degrees celsius single winding |  |  |  |  |  |
| Main Contact Load Current Rating At Maximum Rated Voltage:  |  |  |  |  |  |
| 2.0 amperes ac resistive load and 2.0 amperes dc resistive load                                       |  |  |  |  |  |
| Main Contact Maximum Voltage Rating In Volts:   |  |  |  |  |  |

## NSN 5945-01-157-4611

Electromagnetic Relay - Page 2 of 2



| T | 'nr | ead | <b>Series</b> | Design | ator |
|---|-----|-----|---------------|--------|------|
|   |     |     |               |        |      |

Unc single mounting facility

## **Terminal Type And Quantity:**

8 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A03300