

View Online at <https://aerobasegroup.com/nsn/5945-01-157-9953>

Overall Length:

0.610 inches

Overall Height:

0.507 inches

Overall Width:

0.610 inches

Environmental Protection:

Hermetic

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

975.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Features Provided:

Coil voltage suppression and latching contacts and polarized

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level 1.0 percent

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 pin all functions

Specification Data:

81349-mil-r-39016/35 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300