NSN 5945-01-159-4123

Electromagnetic Relay - Page 1 of 2

Thread Class:

Thread Direction:

Overall Length: 1.374 inches Overall Height: 1.358 inches Overall Width:

2a single mounting facility

Right-hand single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-01-159-4123

0.734 inches
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Thready Qty Per Inch (tpi):
48 single mounting facility
Thread Size:
0.099 inches single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
40.0 milliamperes dc single winding
Time Delay:
1.00 seconds adjustable operate time and 240.00 seconds adjustable operate time

NSN 5945-01-159-4123

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 32.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300