# NSN 5945-01-159-6618

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-159-6618

### **Overall Length:**

5.306 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.806 inches single mounting facility

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility

### **Overall Height:**

1.781 inches

**Overall Width:** 

2.750 inches

**Case Material:** 

Metal

**Environmental Protection:** 

Hermetic and shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

0.144 inches single mounting facility

#### Contact Material:

Silver

#### **Contact Surface Treatment:**

Gold

### Winding Quantity:

1

#### Coil Quantity:

1

## Duty Type:

Continuous

## Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

## Cubic Measure:

25.987 cubic inches

## Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

52 pole, double throw, one position momentary

## Time Delay:

0.045 seconds fixed operate time

## Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

 $5.0 \ \text{amperes} \ \text{ac} \ \text{resistive} \ \text{load} \ \text{and} \ 5.0 \ \text{amperes} \ \text{dc} \ \text{resistive} \ \text{load}$ 

## Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

# NSN 5945-01-159-6618

Electromagnetic Relay - Page 2 of 2



**Precious Material And Location:** 

Contacts silver and contact surfaces and terminals gold

**Precious Material:** 

Gold and silver

Terminal Type And Quantity:

158 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300