NSN 5945-01-159-6618

Electromagnetic Relay - Page 1 of 2

Overall Length:

120.0 ac and 28.0 dc



View Online at https://aerobasegroup.com/nsn/5945-01-159-6618

5.306 inches					
Center To Center Distance Between Mounting Facilities Parallel To Length:					
4.806 inches single mounting facility					
Center To Center Distance Between Mounting Facilities Parallel To Width:					
1.625 inches single mounting facility					
Overall Height:					
1.781 inches					
Overall Width:					
2.750 inches					
Case Material:					
Metal					
Environmental Protection:					
Hermetic and shock resistant and vibration resistant					
Unthreaded Mounting Hole Diameter:					
0.144 inches single mounting facility					
Contact Material:					
Silver					
Contact Surface Treatment:					
Gold					
Winding Quantity:					
1					
Coil Quantity:					
1					
Duty Type:					
Continuous					
Mounting Facility Type And Quantity:					
4 unthreaded hole single mounting facility					
Cubic Measure:					
25.987 cubic inches					
Mounting Facility Pattern:					
Rectangular single mounting facility					
Nonpile-up Main Contact Arrangement:					
52 pole, double throw, one position momentary					
Time Delay:					
0.045 seconds fixed operate time					
Operating Voltage Rating And Type At Specificationified Temp:					
28.0 volts dc 25 degrees celsius single winding					
Main Contact Load Current Rating At Maximum Rated Voltage:					
5.0 amperes ac resistive load and 5.0 amperes dc resistive load					
Main Contact Maximum Voltage Rating In Volts:					

NSN 5945-01-159-6618

Electromagnetic Relay - Page 2 of 2



Draai	aua N	latari:	1 A n d	Location:
rieci	ous IV	าสเษาเ	ai Aiiu	Location.

Contacts silver and contact surfaces and terminals gold

Precious Material:

Gold and silver

Terminal Type And Quantity:

158 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300