

View Online at <https://aerobasegroup.com/nsn/5945-01-160-0893>

Overall Length:

2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility

Overall Height:

3.594 inches

Overall Width:

1.547 inches

Environmental Protection:

Salt spray resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.144 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Height:

3.998 inches single mounting facility

Contact Material:

Silver

Contact Surface Treatment:

Gold

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Magnetic shield and polarized

Cubic Measure:

15.290 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

36 pole, double throw, one position momentary

Time Delay:

0.03 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and terminal surfaces and contact surfaces gold

Precious Material:

Gold and silver

Terminal Type And Quantity:

110 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300