

View Online at <https://aerobasegroup.com/nsn/5945-01-161-8122>

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.188 inches single mounting facility

Overall Height:

1.059 inches

Overall Width:

2.060 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary and 1 pole, single throw, normally open, double make, momentary action

Time Delay:

30.00 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.093 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

135.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300