

View Online at <https://aerobasegroup.com/nsn/5945-01-162-0768>

**Overall Length:**

0.787 inches

**Overall Height:**

0.521 inches

**Overall Width:**

0.366 inches

**Case Material:**

Plastic

**Environmental Protection:**

Shock resistant and vibration resistant

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

1.44 kilohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 plug-in terminal single mounting facility

**Features Provided:**

Polarized

**Cubic Measure:**

0.150 cubic inches

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.003 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

250.0 ac and 220.0 dc

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Precious Material:**

Gold and silver

**Test Data Document:**

98749-8734448 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

8 printed circuit all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300