## NSN 5945-01-162-4012



Electromagnetic Relay - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5945-01-162-4012
Overall Length:
2.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches single mounting facility
Overall Height:
2.187 inches
Overall Width:
1.031 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:

**Contact Material:** 

Silver

**Contact Surface Treatment:** 

0.196 inches single mounting facility

Gold

**Winding Quantity:** 

**Coil Quantity:** 

Winding Dc Resistance Rating:

438.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

2 unthreaded hole single mounting facility

**Cubic Measure:** 

6.482 cubic inches

**Mounting Facility Pattern:** 

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

48 pole, double throw, one position momentary

Time Delay:

0.035 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

**Precious Material And Location:** 

Contacts and terminal surfaces silver and contact surfaces gold

## NSN 5945-01-162-4012

Electromagnetic Relay - Page 2 of 2



Precious Material
-------------------

Gold and silver

**Terminal Type And Quantity:** 

146 quick disconnect, male all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300