## NSN 5945-01-162-6326

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-162-6326
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
2.406 inches
Overall Width:
1.000 inches
Case Material:
Metal
Environmental Protection:
Hermetic and shock resistant and vibration resistant
Frequency In Hertz:
400.0
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Cubic Measure:
3.000 cubic inches
Thready Qty Per Inch (tpi):
40 single mounting facility
Thread Size:
0.112 inches single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.50 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:

operating voltage Rating And Type At C

125.0 volts ac 25 degrees celsius single winding

## NSN 5945-01-162-6326

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 4.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

125.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300