NSN 5945-01-162-6326

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-162-6326

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

2.406 inches

Overall Width:

1.000 inches

Case Material:

Metal

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Cubic Measure:

3.000 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.50 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

125.0 volts ac 25 degrees celsius single winding

NSN 5945-01-162-6326

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 4.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300