

View Online at <https://aerobasegroup.com/nsn/5945-01-163-0171>

Thread Class:

2a single mounting facility

Overall Length:

10.000 inches

Overall Height:

4.630 inches

Overall Width:

6.000 inches

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

3 threaded hole single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

Time Delay:

0.20 seconds fixed operate and release time and 180.00 seconds fixed operate and release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

8.000 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

30.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

30.0 amperes ac resistive load

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

2 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300