# NSN 5945-01-163-1475

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-163-1475

### **Overall Length:**

5.000 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.000 inches single mounting facility

### **Overall Height:**

4.800 inches

#### **Overall Width:**

4.630 inches

#### **Unthreaded Mounting Hole Diameter:**

0.221 inches single mounting facility and 0.231 inches single mounting facility

#### Winding Quantity:

4

#### **Coil Quantity:**

1

## **Duty Type:**

Continuous

### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

### **Mounting Facility Pattern:**

Rectangular single mounting facility

### Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

### **Operating Current Rating And Type:**

250.0 amperes dc single winding

### **Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, momentary action and 5 pole, double throw, one position momentary

### **Auxiliary Contact Maximum Voltage Rating In Volts:**

208.0 ac and 28.0 dc

### Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

### Main Contact Load Current Rating At Maximum Rated Voltage:

250.0 amperes ac inductive load

### **Main Contact Maximum Voltage Rating In Volts:**

208.0 ac

### **Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes dc resistive load

### **Terminal Type And Quantity:**

6 threaded stud all functions

### Shelf Life:

N/a

# NSN 5945-01-163-1475

Electromagnetic Relay - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A03300