

View Online at <https://aerobasegroup.com/nsn/5945-01-165-0453>

Overall Length:

1.280 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

Overall Height:

0.810 inches

Overall Width:

0.810 inches

Mounting Slot Width:

0.133 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Shock resistant and vibration resistant

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

400.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.006 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.062 inches single mounting facility and 1.078 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac motor load and 2.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300