

View Online at <https://aerobasegroup.com/nsn/5945-01-165-5260>

**Overall Length:**

3.700 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.250 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.687 inches single mounting facility

**Overall Height:**

4.576 inches

**Overall Width:**

3.305 inches

**Environmental Protection:**

Shock resistant and vibration resistant and hermetic

**Unthreaded Mounting Hole Diameter:**

0.218 inches single mounting facility

**Frequency In Hertz:**

Between 50.0 and 60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, double make, momentary action

**Operating Current Rating And Type:**

225.0 milliamperes ac single winding

**Time Delay:**

0.065 seconds fixed release time

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action and 1 pole, single throw, normally closed, double break, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

124.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

25.0 amperes ac resistive load and 25.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

750.0 milliamperes ac lamp load and 750.0 milliamperes dc lamp load

**Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

12 threaded stud all functions

**Specification Data:**

96906-ms24143 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-6106 spec.