NSN 5945-01-165-9170

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-165-9170 **Overall Length:** 0.875 inches **Overall Diameter:** 0.370 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 125.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 terminal single mounting facility **Features Provided:** Coil voltage suppression and polarized **Nonpile-up Main Contact Arrangement:** 1 pole, double throw, one position momentary Time Delay: 0.0075 seconds fixed release time Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 100.0 milliamperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Special Features:** Failure rate level 3.0 percent **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 wire lead all functions **Specification Data:** 81349-mil-r-39016/25 government specification Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5945-01-165-9170

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300