

View Online at <https://aerobasegroup.com/nsn/5945-01-169-4124>

**Overall Length:**

1.708 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.412 inches single mounting facility and 1.462 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.000 inches single mounting facility

**Overall Height:**

1.320 inches

**Overall Width:**

1.483 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Environmental Protection:**

Hermetic

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 slotted hole single mounting facility

**Features Provided:**

Polarized

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

6 pole, double throw, one position momentary

**Operating Current Rating And Type:**

180.0 milliamperes dc single winding

**Time Delay:**

0.015 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

20 wire hook all functions

**Specification Data:**

81349-mil-r-6106/8 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300