NSN 5945-01-169-4126

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-169-4126

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.531 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.187 inches single mounting facility

Overall Height:

2.218 inches

Overall Width:

1.531 inches

Environmental Protection:

Shock resistant and vibration resistant

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

180.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

5.199 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

NSN 5945-01-169-4126

Electromagnetic Relay - Page 2 of 2



Operating Current Rating And Type:

100.0 milliamperes dc single winding

Time Delay:

0.02 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

50.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

4.0 amperes ac motor load and 4.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300