NSN 5945-01-170-0448

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-170-0448 **Thread Class:** 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 2.875 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.812 inches single mounting facility **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.500 inches single mounting facility **Overall Height:** 2.937 inches **Overall Width:** 2.343 inches **Environmental Protection:** Hermetic **Contact Material:** Silver **Contact Surface Treatment:** Cadmium plated Winding Quantity: 1 **Coil Quantity:** Winding Dc Resistance Rating: 2.5 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Operating Current Rating And Type:** 9.0 milliamperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp: 32.0 volts dc 25 degrees celsius single winding

NSN 5945-01-170-0448

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load **Main Contact Maximum Voltage Rating In Volts:** 120.0 ac **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 pin all functions Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig: A03300