

View Online at <https://aerobasegroup.com/nsn/5945-01-170-5768>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

1.290 inches

**Overall Width:**

1.025 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Environmental Protection:**

Hermetic and shock resistant and vibration resistant

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Features Provided:**

Polarized

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

14 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300