## NSN 5945-01-171-0129

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-01-171-0129

3.730 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.240 inches single mounting facility and 3.260 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.677 inches single mounting facility and 2.697 inches single mounting facility
Overall Height:
2.501 inches
Overall Width:
3.305 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.218 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
30.831 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, double make, momentary action
Nonpile-up Auxiliary Contact Arrangement:
1 two circuit, double break/double make, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

12.5 amperes ac motor load

## NSN 5945-01-171-0129

Electromagnetic Relay - Page 2 of 2

**Fiig:** A03300



Main Contact Maximum voltage Rating in volts:
440.0 ac
Auxiliary Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes ac resistive load
Terminal Type And Quantity:
12 threaded stud all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No