NSN 5945-01-171-6560

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-171-6560 **Overall Length:** 0.610 inches **Overall Height:** 0.527 inches Overall Width: 0.310 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity: Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Criticality Code Justification:** Feat Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Special Features:** Failure rate level 0.1 percent **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 8 pin all functions **Specification Data:** 81349-mil-r-39016/13 government specification Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5945-01-171-6560

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300