

View Online at <https://aerobasegroup.com/nsn/5945-01-172-9056>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.344 inches single mounting facility and 0.395 inches single mounting facility

Overall Length:

0.928 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.488 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.220 inches single mounting facility

Overall Height:

0.835 inches

Overall Width:

0.800 inches

Environmental Protection:

Shock resistant and vibration resistant and hermetic

Frequency In Hertz:

60.0 or 400.0

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

975.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Features Provided:

Latching contacts

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, both positions maintained

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius all windings and 18.0 volts dc 125 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load and 0.15 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 wire lead all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300